

Artisan Stucco

LIME MORTARS & MATERIALS

Stucco Product & System Finder

INDOOR PROJECT

WHAT MATERIAL ARE YOU PLASTERING ON?

OTHER/I DON'T KNOW

CONTACT YOUR DEALER

BRICKS OR NATURAL STONE

CHOOSE A FINISH

FLOATED FINISH

FRESCO FINISH

WATERPROOF FINISH

YOU WILL NEED

BASE LAYER - ROUGH (BL1)

• 1 x 20 Kg Lime Putty (white)
• 2 x 25 Kg Sand (0-2 mm) ^[2]
per 4-5 m² (thickness: 10-12 mm)

FLOATED LAYER (SL1)

• 1 x 20 Kg Lime Putty (colour)
• 2 x 25 Kg Marble Sand (0-1 mm)
per 7-8 m² (thickness: 3-5 mm)

YOU WILL NEED

BASE LAYER - ROUGH (BL1)

• 1 x 20 Kg Lime Putty (white)
• 2 x 25 Kg Sand (0-2 mm) ^[2]
per 4-5 m² (thickness: 10-12 mm)

FLOATED LAYER (SL1)

• 1 x 20 Kg Lime Putty (colour)
• 2 x 25 Kg Marble Sand (0-1 mm)
per 7-8 m² (thickness: 3-5 mm)

FRESCO LAYER (FL1)

• 1 x 5 L Fine Finish (colour)
per 15 m² (thickness: 0 mm)

YOU WILL NEED

BASE LAYER - ROUGH (BL1)

• 1 x 20 Kg Lime Putty (white)
• 2 x 25 Kg Sand (0-2 mm) ^[2]
per 4-5 m² (thickness: 10-12 mm)

FLOATED LAYER (SL1)

• 1 x 20 Kg Lime Putty (colour)
• 2 x 25 Kg Marble Sand (0-1 mm)
per 7-8 m² (thickness: 3-5 mm)

FRESCO LAYER (FL1)

• 1 x 5 L Fine Finish (colour)
per 15 m² (thickness: 0 mm)

WATERPROOF LAYER (WL1)

• 1 x 1 L WaterProof (colour)
per 10 m² (thickness: 0 mm)

WAX LAYER ^[4]

GYPSUM PLATES, FERMACELL PLATES OR CONCRETE

CHOOSE A FINISH

FLOATED FINISH

FRESCO FINISH

WATERPROOF FINISH

YOU WILL NEED

MINERAL PRIMER ^[1]

BASE LAYER - FINE (BL2)

• 1 x 20 Kg Lime Putty (white)
• 2 x 25 Kg Sand (0-1 mm) ^[3]
per 5-6 m² (thickness: 5-7 mm)
-- Use Stucco Mesh

FLOATED LAYER (SL1)

• 1 x 20 Kg Lime Putty (colour)
• 2 x 25 Kg Marble Sand (0-1 mm)
per 7-8 m² (thickness: 3-5 mm)

YOU WILL NEED

MINERAL PRIMER ^[1]

BASE LAYER - FINE (BL2)

• 1 x 20 Kg Lime Putty (white)
• 2 x 25 Kg Sand (0-1 mm) ^[3]
per 5-6 m² (thickness: 5-7 mm)
-- Use Stucco Mesh

FLOATED LAYER (SL1)

• 1 x 20 Kg Lime Putty (colour)
• 2 x 25 Kg Marble Sand (0-1 mm)
per 7-8 m² (thickness: 3-5 mm)

FRESCO LAYER (FL1)

• 1 x 5 L Fine Finish (colour)
per 15 m² (thickness: 0 mm)

YOU WILL NEED

MINERAL PRIMER ^[1]

BASE LAYER - FINE (BL2)

• 1 x 20 Kg Lime Putty (white)
• 2 x 25 Kg Sand (0-1 mm) ^[3]
per 5-6 m² (thickness: 5-7 mm)
-- Use Stucco Mesh

FLOATED LAYER (SL1)

• 1 x 20 Kg Lime Putty (colour)
• 2 x 25 Kg Marble Sand (0-1 mm)
per 7-8 m² (thickness: 3-5 mm)

FRESCO LAYER (FL1)

• 1 x 5 L Fine Finish (colour)
per 15 m² (thickness: 0 mm)

WATERPROOF LAYER (WL1)

• 1 x 1 L WaterProof (colour)
per 10 m² (thickness: 0 mm)

WAX LAYER ^[4]

[1] Mineral Primer: Use a mineral primer that contains sand for texture.

[2] Sand (0-2 mm): Silicium or Calcium Carbonate (NL: Metselzand)

[3] Sand (0-1 mm): Silicium or Calcium Carbonate (NL: Voegzand)

[4] Wax layer: Recommended for ease of maintenance.

[5] Mineral Impregnation: Recommended for durability of the plaster.

Artisan Stucco

LIME MORTARS & MATERIALS

Stucco Product & System Finder

OUTDOOR PROJECT

WHAT MATERIAL ARE YOU PLASTERING ON?

OTHER/I DON'T KNOW

CONTACT YOUR DEALER

BRICKS OR NATURAL STONE

GYPSUM PLATES, FERMACELL PLATES OR CONCRETE

CHOOSE A FINISH

CHOOSE A FINISH

FLOATED FINISH

FRESCO FINISH

WATERPROOF FINISH

FLOATED FINISH

FRESCO FINISH

WATERPROOF FINISH

YOU WILL NEED

BASE LAYER - ROUGH (BL1)

• 1 x 20 Kg Lime Putty (white)
• 2.5 x 25 Kg Sand (0-2 mm) ^[2]
per 4-5 m² (thickness: 10-12 mm)

FLOATED LAYER (SL1)

• 1 x 20 Kg Lime Putty (colour)
• 2.5 x 25 Kg Marble Sand (0-1 mm)
per 7-8 m² (thickness: 3-5 mm)

MINERAL IMPREGNATION ^[5]

YOU WILL NEED

BASE LAYER - ROUGH (BL1)

• 1 x 20 Kg Lime Putty (white)
• 2.5 x 25 Kg Sand (0-2 mm) ^[2]
per 4-5 m² (thickness: 10-12 mm)

FLOATED LAYER (SL1)

• 1 x 20 Kg Lime Putty (colour)
• 2.5 x 25 Kg Marble Sand (0-1 mm)
per 7-8 m² (thickness: 3-5 mm)

FRESCO LAYER (FL1)

• 1 x 5 L Fine Finish (colour)
per 15 m² (thickness: 0 mm)

MINERAL IMPREGNATION ^[5]

YOU WILL NEED

BASE LAYER - ROUGH (BL1)

• 1 x 20 Kg Lime Putty (white)
• 2.5 x 25 Kg Sand (0-2 mm) ^[2]
per 4-5 m² (thickness: 10-12 mm)

FLOATED LAYER (SL1)

• 1 x 20 Kg Lime Putty (colour)
• 2.5 x 25 Kg Marble Sand (0-1 mm)
per 7-8 m² (thickness: 3-5 mm)

FRESCO LAYER (FL1)

• 1 x 5 L Fine Finish (colour)
per 15 m² (thickness: 0 mm)

WATERPROOF LAYER (WL1)

• 1 x 1 L WaterProof (colour)
per 10 m² (thickness: 0 mm)

MINERAL IMPREGNATION ^[5]

YOU WILL NEED

MINERAL PRIMER ^[1]

BASE LAYER - FINE (BL2)

• 1 x 20 Kg Lime Putty (white)
• 2.5 x 25 Kg Sand (0-1 mm) ^[3]
per 5-6 m² (thickness: 5-7 mm)
-- Use Stucco Mesh

FLOATED LAYER (SL1)

• 1 x 20 Kg Lime Putty (colour)
• 2.5 x 25 Kg Marble Sand (0-1 mm)
per 7-8 m² (thickness: 3-5 mm)

MINERAL IMPREGNATION ^[5]

YOU WILL NEED

MINERAL PRIMER ^[1]

BASE LAYER - FINE (BL2)

• 1 x 20 Kg Lime Putty (white)
• 2.5 x 25 Kg Sand (0-1 mm) ^[3]
per 5-6 m² (thickness: 5-7 mm)
-- Use Stucco Mesh

FLOATED LAYER (SL1)

• 1 x 20 Kg Lime Putty (colour)
• 2.5 x 25 Kg Marble Sand (0-1 mm)
per 7-8 m² (thickness: 3-5 mm)

FRESCO LAYER (FL1)

• 1 x 5 L Fine Finish (colour)
per 15 m² (thickness: 0 mm)

MINERAL IMPREGNATION ^[5]

YOU WILL NEED

MINERAL PRIMER ^[1]

BASE LAYER - FINE (BL2)

• 1 x 20 Kg Lime Putty (white)
• 2.5 x 25 Kg Sand (0-1 mm) ^[3]
per 5-6 m² (thickness: 5-7 mm)
-- Use Stucco Mesh

FLOATED LAYER (SL1)

• 1 x 20 Kg Lime Putty (colour)
• 2.5 x 25 Kg Marble Sand (0-1 mm)
per 7-8 m² (thickness: 3-5 mm)

FRESCO LAYER (FL1)

• 1 x 5 L Fine Finish (colour)
per 15 m² (thickness: 0 mm)

WATERPROOF LAYER (WL1)

• 1 x 1 L WaterProof (colour)
per 10 m² (thickness: 0 mm)

MINERAL IMPREGNATION ^[5]

[1] Mineral Primer: Use a mineral primer that contains sand for texture.

[2] Sand (0-2 mm): Silicium or Calcium Carbonate (NL: Metselzand)

[3] Sand (0-1 mm): Silicium or Calcium Carbonate (NL: Voegzand)

[4] Wax layer: Recommended for ease of maintenance.

[5] Mineral Impregnation: Recommended for durability of the plaster.